



SUMMER, SIRÉN OCH KOMBISIGNAL KLH (KDH)

710100005

KLH Summer/Sirén med tratt 92 dB 24 V DC

- Membransummer
- 92 dB
- -25°C / +50°C
- IP43 & NEMA type 2
- Steady tone



PRODUKTBESKRIVNING

Liten membransummer till låg kostnad för inomhusbruk.

Finns även i fler spänningsutföranden mot förfrågan.

TEKNISK DATA

Antal toner	1 st
Färg hus	Grå RAL 7035
IP-klass	IP43, NEMA Type 2
Kabelingång	Baksidan
Ljudnivå max	92 dB
Ljudnivå min	92 dB
Matningsspänning	24 V
Matningsspänning DC max	26,4 V DC
Matningsspänning DC min	21,6 V DC
Montering	Vertikal
Nominell ström max	0,026 A
Nominell ström min	0,026 A
Plintanslutning	2,5 mm ²

Temperaturområde från -25 °C

Temperaturområde till 50 °C

Tonfrekvens max 50 Hz

Tonfrekvens min 50 Hz

Vikt 180 g

The sound pressure decreases by 6 dB when doubling the distance, the following distance table is to be seen as indication, as also factors like tone type, wind speed, wind direction, humidity, weather conditions etc. do influence the sound pressure level.

Distance (m)	Sound pressure dB (A)																				
1	85	70	75	80	85	90	92	94	96	98	100	102	104	106	108	110	112	114	116	118	120
2	59	64	69	74	79	84	86	88	90	92	94	96	98	100	102	104	106	108	110	112	114
3	50	60	65	70	75	80	82	84	86	88	90	92	94	96	98	100	102	104	106	108	110
5	51	56	61	66	71	76	78	80	82	84	86	88	90	92	94	96	98	100	102	104	106
10	45	50	55	60	65	70	72	74	76	78	80	82	84	86	88	90	92	94	96	98	100
20	39	44	49	54	59	64	66	68	70	72	74	76	78	80	82	84	86	88	90	92	94
30	35	40	45	50	55	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88	90
50	36	41	46	51	56	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88	90
100				40	45	50	52	54	56	58	60	62	64	66	68	70	72	74	76	78	80
200				39	44	48	50	52	54	56	58	60	62	64	66	68	70	72	74	76	78
500				38	40	42	44	46	48	50	52	54	56	58	60	62	64	66	68	70	72

The sound pressure decreases by 6 dB when doubling the distance

